

PRYAN Platinum Fire-Rated Glass Ceramics



PYRAN® Platinum Fire-Rated Glass-Ceramics Listings Table

PYRAN® glass-ceramic type	Rating (minutes)	Location	Max. exposed area of glazing (in ²)	Max. width of exposed glazing (inches)	Max. height exposed glazing (inches)	Min. depth of groove (inches)	Impact Safety Rated
PYRAN® Platinum	Up to 90	Other than doors	3,422 (23.7 ft ²)	76	76	5/8	No
PYRAN® Platinum F	Up to 90	Doors non-temp rise	2,736 (19 ft ²)	36	76	5/8	Yes
	Up to 180	Doors temp rise and non-temp	100 (0.69 ft ²)	12	33	1/2	Yes
	Up to 90	Other than doors	3,422 (23.7 ft ²)	76	76	5/8	Yes
PYRAN® Platinum L	Up to 90	Doors non-temp rise	2,736 (19 ft ²)	36	75	5/8	Yes
	Up to 180	Doors temp rise and non-temp rise	100 (0.69 ft ²)	12	75	1/2	Yes
	Up to 90	Other than doors	3,143 (21.8 ft ²)	75	75	5/8	Yes



FIRE TESTED



HOSE-STREAM TESTED



IMPACT TESTED



14242 C Circle • Omaha, NE 68144 • Toll Free (800) 383-4527 • Fax (402) 339-9395

QualityGlassOmaha.com • sales@qualglass.com